

## e-STUDIO™ 6529A/7529A/9029A

Introducing a new generation of Toshiba MFPs – with high-performance, zero-trust security and cloud-ready features, these printers are the perfect choice for today's modern work environments.

- High-Speed – Up to 65, 75 & 90 PPM
- High-Volume
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



# e-STUDIO™ 6529A/7529A/9029A

## MAIN SPECIFICATIONS

<b>Copy Process</b>	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
<b>Display</b>	10.1" Color WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	65/75/90 PPM (LT)
<b>First Copy Out</b>	Monochrome: Less Than 5.2/4.5/4.1 Seconds
<b>Warm-Up Time</b>	From Powering On: Approx. 20/24/25 Seconds From Sleep: 15.4/15.4/Less Than 20 Seconds From Low Power: 15.4 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 3,520 Sheets/Max. 8,020 Sheets
<b>Original Feed</b>	300-Sheet DSDf with Double Feed Detection
<b>Max. Original Size</b>	LD/A3
<b>Paper Feed Sizes</b>	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF: 1,160 x 2 LT Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet External LCF LT Only Opt. 2,000-Sheet Piggyback External LCF LT Only Drawers: Standard 540 Sheets x 2-16lb Bond-110lb Cover Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index)
<b>Paper Weights</b>	25% to 400% Max. 590K/660K/740K Month Approx. 430lb 37.6" (W) x 27.5" (D) x 48.3" (H) 106.6K @ 5% 120 Volts, 50/60 Hz, 16 Amps Maximum 2.0kW/2.0kW/2.4kW (120V)
<b>Duplex</b>	NEMA 5-20
<b>Reproduction Ratio</b>	6GB
<b>Max Duty Cycle</b>	128GB Solid State Drive (SSD)
<b>Weight</b>	
<b>Approx. Dimensions</b>	
<b>Toner Yield</b>	
<b>Power Source</b>	
<b>Power Consumption</b>	
<b>Plug Type</b>	
<b>Memory</b>	
<b>Hard Disk Drive</b>	

## e-BRIDGE NEXT PRINT SPECIFICATIONS

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Resolution</b>	600 x 600 dpi, 1,200 x 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (with Smoothing) (PS3 Only)
<b>Operating Systems</b>	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
<b>Network Protocols</b>	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
<b>Printing Protocols</b>	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
<b>Print Drivers</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Interface</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Wireless Device</b>	TopAccess
<b>Device Management</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Account Control</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist
<b>Accessibility Features</b>	



## Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite\*, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication \*Conformance with HCD-PPV1.0 in High Security Mode

## Environmental Standards Certifications

ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

## SCAN SPECIFICATIONS

<b>Scan Speed</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
<b>Scan Weights</b>	9.3-110lb Bond
<b>Scan Modes</b>	Standard: Full Color, Auto Color, Monochrome, Grayscale
<b>OCR</b>	DOC/XLS/PPT/PDF
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
<b>Image Compression</b>	Color/Grayscale: JPEG (High, Middle, Low)

## FACSIMILE SPECIFICATIONS

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job

## e-FILING SPECIFICATIONS

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## ACCESSORIES (OPTIONS)

<b>Additional Paper Options</b>		<b>Miscellaneous Options</b>	
Large Capacity Feeder - 2,500 Sheet	MP2503L	Card Reader Holder	GR1320
Large Capacity Feeder - 2,000 Sheet	MP2002L	Accessory Tray	GR1330
LCF Connector (to Add 2K LCF)	KN9000	Panel 10-Key Option	GR1340
<b>Finishing Options</b>		Manual Pocket	KK5008
65-Sheet Staple Finisher	MJ1115	Harness for Coin Controller	GQ1280
65-Sheet Saddle-Stitch Finisher	MJ1116	Accessible Arm	KK2560
Hole Punch for MJ1115/MJ1116	MJ6108N	<b>Software Options</b>	
Finisher Guide Rail	KN1103	e-BRIDGE Global Print	GB2550NODE
Exit Tray	KA6551	IPSec Enabler	GP1080NODE
<b>Connectivity/Security Options</b>		Unicode Font Enabler	GS1007NODE
FAX Unit/2 <sup>nd</sup> Line for FAX Unit	GD1370N	Multi-Station Print Enabler	
Wireless LAN/Bluetooth	GN4030A3	Per Seat License	GS1090NODE
Fax Over IP License Key	GS1100NODE	e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Bluetooth Keyboard	GR9001	e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
2 <sup>nd</sup> NIC Holder	GR1430	e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
USB Hub	GR1420	Workplace Productivity Bundle e-BRIDGE Plus for Gmail e-BRIDGE Plus for Google Workspace	GB2330NODE GB2380NODE GB2390NODE
Meta Scan Enabler	GS1010NODE	e-BRIDGE Plus Voice Guidance	GB2540NODE
Security SSD (512GB)	GE1280		
FIPS HDD (320GB)	GE1260		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

## Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## Website

business.toshiba.com